



US008699215B2

(12) **United States Patent**
Whitt, III et al.

(10) **Patent No.:** **US 8,699,215 B2**

(45) **Date of Patent:** **Apr. 15, 2014**

(54) **FLEXIBLE HINGE SPINE**

(75) Inventors: **David Otto Whitt, III**, Sammamish, WA (US); **Eric Joseph Wahl**, Kirkland, WA (US); **David C. Vandervoort**, Seattle, WA (US); **Todd David Pleake**, Sammamish, WA (US); **Rob Huala**, Bellevue, WA (US); **Summer L. Schneider**, Seattle, WA (US); **Robyn Rebecca Reed McLaughlin**, Seattle, WA (US); **Matthew David Mickelson**, Seattle, WA (US); **Joel Lawrence Pelley**, Bellevue, WA (US); **Timothy C. Shaw**, Sammamish, WA (US); **Ralf Groene**, Kirkland, WA (US); **Hua Wang**, Sammamish, WA (US); **Christopher Harry Stoumbos**, Sammamish, WA (US); **Karsten Aagaard**, Monroe, WA (US)

(73) Assignee: **Microsoft Corporation**, Redmond, WA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/563,435**

(22) Filed: **Jul. 31, 2012**

(65) **Prior Publication Data**

US 2013/0301199 A1 Nov. 14, 2013

Related U.S. Application Data

(63) Continuation of application No. 13/470,633, filed on May 14, 2012, now Pat. No. 8,498,100.

(51) **Int. Cl.**
H05K 7/00 (2006.01)

(52) **U.S. Cl.**
 USPC **361/679.21**; 361/679.27; 361/679.28;
 361/679.29; 361/679.3; 361/679.43; 361/679.58;
 345/169

(58) **Field of Classification Search**

USPC 361/679.09, 679.15, 679.17,
 361/679.27–679.29; 345/168, 169; 400/472
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

578,325 A 3/1897 Fleming
 (Continued)

FOREIGN PATENT DOCUMENTS

CN 103455149 12/2013
 (Continued)

OTHER PUBLICATIONS

“ACPI Docking for Windows Operating Systems”, Retrieved from:
 <<http://www.scribube.com/limba/engleza/software/ACPI-Docking-for-Windows-Opera331824193.php>> on Jul. 6, 2012, 10 pages.

(Continued)


Primary Examiner — Ramon Barrera

(74) *Attorney, Agent, or Firm* — Tony Azure; Andrew Sanders; Micky Minhas

(57) **ABSTRACT**

Flexible hinge spine techniques are described. In one or more implementations, a flexible hinge is configured to communicatively and physically couple an input device to a computing device and may implement functionality such as a support layer and minimum bend radius. The input device may also include functionality to promote a secure physical connection between the input device and the computing device. One example of this includes use of one or more protrusions that are configured to be removed from respective cavities of the computing device along a particular axis but mechanically bind along other axes. Other techniques include use of a laminate structure to form a connection portion of the input device.

19 Claims, 14 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

4,046,975 A	9/1977	Seeger, Jr.	6,976,799 B2	12/2005	Kim et al.
4,065,649 A	12/1977	Carter et al.	7,051,149 B2	5/2006	Wang et al.
4,243,861 A	1/1981	Strandwitz	7,083,295 B1	8/2006	Hanna
4,302,648 A	11/1981	Sado et al.	7,091,436 B2	8/2006	Serban
4,317,013 A	2/1982	Larson	7,106,222 B2	9/2006	Ward et al.
4,365,130 A	12/1982	Christensen	7,123,292 B1	10/2006	Seeger et al.
4,492,829 A	1/1985	Rodrique	7,194,662 B2	3/2007	Do et al.
4,527,021 A	7/1985	Morikawa et al.	7,213,991 B2	5/2007	Chapman et al.
4,559,426 A	12/1985	Van Zeeland et al.	7,277,087 B2	10/2007	Hill et al.
4,577,822 A	3/1986	Wilkerson	7,301,759 B2	11/2007	Hsiung
4,588,187 A	5/1986	Dell	7,447,934 B2	11/2008	Dasari et al.
4,607,147 A	8/1986	Ono et al.	7,469,386 B2	12/2008	Bear et al.
4,651,133 A	3/1987	Ganesan et al.	7,486,165 B2	2/2009	Ligtenberg et al.
4,735,394 A	4/1988	Facco	7,499,037 B2	3/2009	Lube
5,008,497 A	4/1991	Asher	7,502,803 B2	3/2009	Culter et al.
5,220,521 A	6/1993	Kikinis	7,542,052 B2	6/2009	Solomon et al.
5,283,559 A	2/1994	Kalendra et al.	7,558,594 B2	7/2009	Wilson
5,331,443 A	7/1994	Stanisci	7,559,834 B1	7/2009	York
5,480,118 A	1/1996	Cross	RE40,891 E	9/2009	Yasutake
5,546,271 A	8/1996	Gut et al.	7,636,921 B2	12/2009	Louie
5,548,477 A	8/1996	Kumar et al.	7,656,392 B2	2/2010	Bolender
5,558,577 A	9/1996	Kato	7,731,147 B2	6/2010	Rha
5,576,981 A	11/1996	Parker et al.	7,733,326 B1	6/2010	Adiseshan
5,618,232 A	4/1997	Martin	7,773,076 B2	8/2010	Pittel et al.
5,681,220 A	10/1997	Bertram et al.	7,777,972 B1	8/2010	Chen et al.
5,745,376 A	4/1998	Barker et al.	7,782,342 B2	8/2010	Koh
5,748,114 A	5/1998	Koehn	7,813,715 B2	10/2010	McKillop et al.
5,781,406 A	7/1998	Hunte	7,822,338 B2	10/2010	Wernersson
5,807,175 A	9/1998	Davis et al.	7,865,639 B2	1/2011	McCoy et al.
5,818,361 A	10/1998	Acevedo	7,884,807 B2	2/2011	Hovden et al.
5,828,770 A	10/1998	Leis et al.	D636,397 S	4/2011	Green
5,842,027 A	11/1998	Oprescu et al.	7,928,964 B2	4/2011	Kolmykov-Zotov et al.
5,874,697 A	2/1999	Selker et al.	7,945,717 B2	5/2011	Rivalsi
5,926,170 A	7/1999	Oba	7,973,771 B2	7/2011	Geaghan
5,971,635 A	10/1999	Wise	7,978,281 B2	7/2011	Vergith et al.
6,002,389 A	12/1999	Kasser	8,016,255 B2	9/2011	Lin
6,005,209 A	12/1999	Burleson et al.	8,053,688 B2	11/2011	Conzola et al.
6,012,714 A	1/2000	Worley et al.	8,065,624 B2	11/2011	Morin et al.
6,040,823 A	3/2000	Seffernick et al.	8,069,356 B2	11/2011	Rathi et al.
6,044,717 A	4/2000	Biegelsen et al.	8,090,885 B2	1/2012	Callaghan et al.
6,061,644 A	5/2000	Leis	8,098,233 B2	1/2012	Hotelling et al.
6,112,797 A	9/2000	Colson et al.	8,115,499 B2	2/2012	Osoinach et al.
6,178,443 B1	1/2001	Lin	8,117,362 B2	2/2012	Rodriguez et al.
6,254,105 B1	7/2001	Rinde et al.	8,118,274 B2	2/2012	McClure et al.
6,279,060 B1	8/2001	Luke et al.	8,130,203 B2	3/2012	Westerman
6,329,617 B1	12/2001	Burgess	8,154,524 B2	4/2012	Wilson et al.
6,344,791 B1	2/2002	Armstrong	8,162,282 B2	4/2012	Hu et al.
6,380,497 B1	4/2002	Hashimoto et al.	D659,139 S	5/2012	Gengler
6,437,682 B1	8/2002	Vance	8,169,421 B2	5/2012	Wright et al.
6,511,378 B1	1/2003	Bhatt et al.	8,229,509 B2	7/2012	Paek et al.
6,532,147 B1	3/2003	Christ, Jr.	8,229,522 B2	7/2012	Kim et al.
6,543,949 B1	4/2003	Ritchey et al.	8,248,791 B2	8/2012	Wang et al.
6,565,439 B2	5/2003	Shinohara et al.	8,255,708 B1	8/2012	Zhang
6,597,347 B1	7/2003	Yasutake	8,267,368 B2	9/2012	Torii et al.
6,600,121 B1	7/2003	Olodort et al.	8,274,784 B2	9/2012	Franz et al.
6,603,408 B1	8/2003	Gaba	8,279,589 B2	10/2012	Kim
6,617,536 B2	9/2003	Kawaguchi	8,322,290 B1	12/2012	Mignano
6,651,943 B2	11/2003	Cho et al.	8,416,559 B2	4/2013	Agata et al.
6,685,369 B2	2/2004	Lien	8,498,100 B1	7/2013	Whitt, III et al.
6,695,273 B2	2/2004	Iguchi	8,543,227 B1	9/2013	Perek et al.
6,704,864 B1	3/2004	Philyaw	8,548,608 B2	10/2013	Perek et al.
6,721,019 B2	4/2004	Kono et al.	8,564,944 B2	10/2013	Whitt, III et al.
6,725,318 B1	4/2004	Sherman et al.	8,570,725 B2	10/2013	Whitt, III et al.
6,774,888 B1	8/2004	Genduso	8,610,015 B2	12/2013	Whitt et al.
6,776,546 B2	8/2004	Kraus et al.	8,614,666 B2	12/2013	Whitman et al.
6,781,819 B2	8/2004	Yang et al.	8,646,999 B2	2/2014	Shaw et al.
6,784,869 B1	8/2004	Clark et al.	2002/0134828 A1	9/2002	Sandbach et al.
6,813,143 B2	11/2004	Makela	2002/0163510 A1	11/2002	Williams et al.
6,819,316 B2	11/2004	Schulz et al.	2003/0132916 A1	7/2003	Kramer
6,856,506 B2	2/2005	Doherty et al.	2003/0163611 A1	8/2003	Nagao
6,861,961 B2	3/2005	Sandbach et al.	2003/0197687 A1	10/2003	Shetter
6,898,315 B2	5/2005	Guha	2004/0100457 A1	5/2004	Mandle
6,914,197 B2	7/2005	Doherty et al.	2004/0258924 A1	12/2004	Berger et al.
6,950,950 B2	9/2005	Sawyers et al.	2004/0268000 A1	12/2004	Barker et al.
6,970,957 B1	11/2005	Oshins et al.	2005/0030728 A1	2/2005	Kawashima et al.
			2005/0057515 A1	3/2005	Bathiche
			2005/0059489 A1	3/2005	Kim
			2005/0134717 A1	6/2005	Misawa
			2005/0146512 A1	7/2005	Hill et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0264653	A1	12/2005	Starkweather et al.	2010/0156798	A1	6/2010	Archer
2005/0264988	A1	12/2005	Nicolosi	2010/0161522	A1	6/2010	Tirpak et al.
2005/0285703	A1	12/2005	Wheeler et al.	2010/0164857	A1	7/2010	Liu et al.
2006/0085658	A1	4/2006	Allen et al.	2010/0171891	A1	7/2010	Kaji et al.
2006/0125799	A1	6/2006	Hillis et al.	2010/0174421	A1	7/2010	Tsai et al.
2006/0154725	A1	7/2006	Glaser et al.	2010/0180063	A1	7/2010	Ananny et al.
2006/0156415	A1	7/2006	Rubinstein et al.	2010/0188299	A1	7/2010	Rinehart et al.
2006/0181514	A1	8/2006	Newman	2010/0188338	A1	7/2010	Longe
2006/0187216	A1	8/2006	Trent, Jr. et al.	2010/0206614	A1	8/2010	Park et al.
2006/0195522	A1	8/2006	Miyazaki	2010/0214214	A1	8/2010	Corson et al.
2006/0238510	A1	10/2006	Panotopoulos et al.	2010/0214257	A1	8/2010	Wussler et al.
2007/0056385	A1	3/2007	Lorenz	2010/0222110	A1	9/2010	Kim et al.
2007/0062089	A1	3/2007	Homer et al.	2010/0245221	A1	9/2010	Khan
2007/0069153	A1	3/2007	Pai-Paranjape et al.	2010/0250988	A1	9/2010	Okuda et al.
2007/0072474	A1	3/2007	Beasley et al.	2010/0274932	A1	10/2010	Kose
2007/0145945	A1	6/2007	McGinley et al.	2010/0279768	A1	11/2010	Huang et al.
2007/0182663	A1	8/2007	Biech	2010/0289457	A1	11/2010	Onnerud et al.
2007/0182722	A1	8/2007	Hotelling et al.	2010/0295812	A1	11/2010	Burns et al.
2007/0188478	A1	8/2007	Silverstein et al.	2010/0302378	A1	12/2010	Marks et al.
2007/0200830	A1	8/2007	Yamamoto	2010/0304793	A1	12/2010	Kim
2007/0220708	A1	9/2007	Lewis	2010/0306538	A1	12/2010	Thomas et al.
2007/0234420	A1	10/2007	Novotney et al.	2010/0308778	A1	12/2010	Yamazaki et al.
2007/0236408	A1	10/2007	Yamaguchi et al.	2010/0308844	A1	12/2010	Day et al.
2007/0236475	A1	10/2007	Wherry	2010/0315348	A1	12/2010	Jellicoe et al.
2007/0247338	A1	10/2007	Marchetto	2010/0325155	A1	12/2010	Skinner et al.
2007/0247432	A1	10/2007	Oakley	2010/0331059	A1	12/2010	Apgar et al.
2007/0260892	A1	11/2007	Paul et al.	2011/0012873	A1	1/2011	Prest et al.
2007/0283179	A1	12/2007	Burnett et al.	2011/0019123	A1	1/2011	Prest et al.
2008/0005423	A1	1/2008	Jacobs et al.	2011/0031287	A1	2/2011	Le Gette et al.
2008/0104437	A1	5/2008	Lee	2011/0036965	A1	2/2011	Zhang et al.
2008/0151478	A1	6/2008	Chern	2011/0037721	A1	2/2011	Cranfill et al.
2008/0158185	A1	7/2008	Westerman	2011/0043990	A1	2/2011	Mickey et al.
2008/0174570	A1	7/2008	Jobs et al.	2011/0055407	A1	3/2011	Lydon et al.
2008/0180411	A1	7/2008	Solomon et al.	2011/0060926	A1	3/2011	Brooks et al.
2008/0228969	A1	9/2008	Cheah et al.	2011/0069148	A1	3/2011	Jones et al.
2008/0238884	A1	10/2008	Harish	2011/0074688	A1	3/2011	Hull et al.
2008/0253822	A1	10/2008	Matias	2011/0102326	A1	5/2011	Casparian et al.
2008/0316002	A1	12/2008	Brunet et al.	2011/0102356	A1	5/2011	Kemppinen et al.
2008/0320190	A1	12/2008	Lydon et al.	2011/0134032	A1	6/2011	Chiu et al.
2009/0007001	A1	1/2009	Morin et al.	2011/0157087	A1	6/2011	Kanehira et al.
2009/0009476	A1	1/2009	Daley, III	2011/0163955	A1	7/2011	Nasiri et al.
2009/0073957	A1	3/2009	Newland et al.	2011/0164370	A1	7/2011	McClure et al.
2009/0083562	A1	3/2009	Park et al.	2011/0167181	A1	7/2011	Minoo et al.
2009/0140985	A1	6/2009	Liu	2011/0167287	A1	7/2011	Walsh et al.
2009/0167728	A1	7/2009	Geaghan et al.	2011/0167391	A1	7/2011	Momeyer et al.
2009/0195497	A1	8/2009	Fitzgerald et al.	2011/0167992	A1	7/2011	Eventoff et al.
2009/0231275	A1	9/2009	Odgers	2011/0179864	A1	7/2011	Raasch et al.
2009/0251008	A1	10/2009	Sugaya	2011/0184646	A1	7/2011	Wong et al.
2009/0259865	A1	10/2009	Sheynblat et al.	2011/0193787	A1	8/2011	Morishige et al.
2009/0262492	A1	10/2009	Whitchurch et al.	2011/0205372	A1	8/2011	Miramontes
2009/0265670	A1	10/2009	Kim et al.	2011/0227913	A1	9/2011	Hyndman
2009/0303137	A1	12/2009	Kusaka et al.	2011/0231682	A1	9/2011	Kakish et al.
2009/0303204	A1	12/2009	Nasiri et al.	2011/0234502	A1	9/2011	Yun et al.
2009/0320244	A1	12/2009	Lin	2011/0248152	A1	10/2011	Svajda et al.
2009/0321490	A1	12/2009	Groene et al.	2011/0248920	A1	10/2011	Larsen
2010/0001963	A1	1/2010	Doray et al.	2011/0248941	A1	10/2011	Abdo et al.
2010/0013319	A1	1/2010	Kamiyama et al.	2011/0261001	A1	10/2011	Liu
2010/0026656	A1	2/2010	Hotelling et al.	2011/0267272	A1	11/2011	Meyer et al.
2010/0038821	A1	2/2010	Jenkins et al.	2011/0290686	A1	12/2011	Huang
2010/0045609	A1	2/2010	Do et al.	2011/0295697	A1	12/2011	Boston et al.
2010/0045633	A1	2/2010	Gettemy	2011/0297566	A1	12/2011	Gallagher et al.
2010/0051356	A1	3/2010	Stern et al.	2011/0304577	A1	12/2011	Brown et al.
2010/0051432	A1	3/2010	Lin et al.	2011/0316807	A1	12/2011	Corrion
2010/0053534	A1	3/2010	Hsieh et al.	2012/0007821	A1	1/2012	Zaliva
2010/0077237	A1	3/2010	Sawyers	2012/0023459	A1	1/2012	Westerman
2010/0081377	A1	4/2010	Chatterjee et al.	2012/0024682	A1	2/2012	Huang et al.
2010/0085321	A1	4/2010	Pundsack	2012/0044179	A1	2/2012	Hudson
2010/0102182	A1	4/2010	Lin	2012/0047368	A1	2/2012	Chinn et al.
2010/0103112	A1	4/2010	Yoo et al.	2012/0050975	A1	3/2012	Garelli et al.
2010/0123686	A1	5/2010	Klinghult et al.	2012/0068919	A1	3/2012	Lauder et al.
2010/0133398	A1	6/2010	Chiu et al.	2012/0075249	A1	3/2012	Hoch
2010/0142130	A1	6/2010	Wang et al.	2012/0092279	A1	4/2012	Martin
2010/0149111	A1	6/2010	Olien	2012/0094257	A1	4/2012	Pillischer et al.
2010/0149134	A1	6/2010	Westerman et al.	2012/0099749	A1	4/2012	Rubin et al.
2010/0149377	A1	6/2010	Shintani et al.	2012/0113579	A1	5/2012	Agata et al.
				2012/0117409	A1	5/2012	Lee et al.
				2012/0127118	A1	5/2012	Nolting et al.
				2012/0140396	A1	6/2012	Zeliff et al.
				2012/0145525	A1	6/2012	Ishikawa

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0162693 A1 6/2012 Ito
 2012/0175487 A1 7/2012 Goto
 2012/0182242 A1 7/2012 Lindahl et al.
 2012/0194448 A1 8/2012 Rothkopf
 2012/0224073 A1 9/2012 Miyahara
 2012/0246377 A1 9/2012 Bhesania et al.
 2012/0256959 A1 10/2012 Ye et al.
 2012/0274811 A1 11/2012 Bakin
 2012/0300275 A1 11/2012 Vilardell et al.
 2012/0312955 A1 12/2012 Randolph
 2013/0009413 A1 1/2013 Chiu et al.
 2013/0063873 A1 3/2013 Wodrich et al.
 2013/0088431 A1 4/2013 Ballagas et al.
 2013/0106766 A1 5/2013 Yilmaz et al.
 2013/0207937 A1 8/2013 Lutian
 2013/0227836 A1 9/2013 Whitt, III
 2013/0228023 A1 9/2013 Drasnin
 2013/0228433 A1 9/2013 Shaw
 2013/0228434 A1 9/2013 Whitt, III
 2013/0228435 A1 9/2013 Whitt, III
 2013/0228439 A1 9/2013 Whitt, III
 2013/0229100 A1 9/2013 Siddiqui
 2013/0229335 A1 9/2013 Whitman
 2013/0229347 A1 9/2013 Lutz, III
 2013/0229350 A1 9/2013 Shaw
 2013/0229351 A1 9/2013 Whitt, III
 2013/0229354 A1 9/2013 Whitt, III
 2013/0229356 A1 9/2013 Marwah
 2013/0229363 A1 9/2013 Whitman
 2013/0229366 A1 9/2013 Dighde
 2013/0229380 A1 9/2013 Lutz, III
 2013/0229386 A1 9/2013 Bathiche
 2013/0229534 A1 9/2013 Panay
 2013/0229568 A1 9/2013 Belesiu
 2013/0229570 A1 9/2013 Beck
 2013/0229756 A1 9/2013 Whitt, III
 2013/0229757 A1 9/2013 Whitt, III
 2013/0229758 A1 9/2013 Belesiu
 2013/0229759 A1 9/2013 Whitt, III
 2013/0229760 A1 9/2013 Whitt, III
 2013/0229761 A1 9/2013 Shaw
 2013/0229762 A1 9/2013 Whitt, III
 2013/0229773 A1 9/2013 Siddiqui
 2013/0230346 A1 9/2013 Shaw
 2013/0231755 A1 9/2013 Perek
 2013/0232280 A1 9/2013 Perek
 2013/0232348 A1 9/2013 Oler
 2013/0232349 A1 9/2013 Oler
 2013/0232353 A1 9/2013 Belesiu
 2013/0232571 A1 9/2013 Belesiu
 2013/0242495 A1 9/2013 Bathiche et al.
 2013/0300590 A1 11/2013 Dietz
 2013/0300647 A1 11/2013 Drasnin
 2013/0301206 A1 11/2013 Whitt
 2013/0304941 A1 11/2013 Drasnin
 2013/0322000 A1 12/2013 Whitt
 2013/0322001 A1 12/2013 Whitt
 2013/0332628 A1 12/2013 Panay
 2014/0012401 A1 1/2014 Perek

FOREIGN PATENT DOCUMENTS

EP 1223722 7/2002
 EP 1591891 11/2005
 EP 2353978 8/2011
 GB 2123213 1/1984
 GB 2178570 2/1987
 JP 56108127 8/1981
 JP 10326124 12/1998
 JP 1173239 3/1999
 JP 2006294361 10/2006
 KR 1020110087178 8/2011

NL 1038411 5/2012
 WO WO-2006044818 4/2006
 WO WO-2010011983 1/2010

OTHER PUBLICATIONS

"Corrected Notice of Allowance", U.S. Appl. No. 13/470,633, (Apr. 9, 2013), 2 pages.
 "DR2PA", retrieved from <http://www.architainment.co.uk/wp-content/uploads/2012/08/DR2PA-AU-US-size-Data-Sheet-Rev-H_LOGO.pdf> on Sep. 17, 2012, 4 pages.
 "Final Office Action", U.S. Appl. No. 13/651,195, (Apr. 18, 2013), 13 pages.
 "Final Office Action", U.S. Appl. No. 13/651,232, (May 21, 2013), 21 pages.
 "Final Office Action", U.S. Appl. No. 13/651,287, (May 3, 2013), 16 pages.
 "NI Releases New Maschine & Maschine Mikro", Retrieved from <<http://www.djbooth.net/index/dj-equipment/entry/ni-releases-new-maschine-mikro/>> on Sep. 17, 2012, 19 pages.
 "Non-Final Office Action", U.S. Appl. No. 13/651,726, (Apr. 15, 2013), 6 pages.
 "Non-Final Office Action", U.S. Appl. No. 13/656,055, (Apr. 23, 2013), 11 pages.
 "Notice of Allowance", U.S. Appl. No. 13/471,202, (May 28, 2013), 7 pages.
 "Notice of Allowance", U.S. Appl. No. 13/651,272, (May 2, 2013), 7 pages.
 Das, Apurba et al., "Study of Heat Transfer through Multilayer Clothing Assemblies: A Theoretical Prediction", Retrieved from <http://www.autexrj.com/cms/zalaczone_pliki/5_013_11.pdf>, (Jun. 2011), 7 pages.
 Iwase, Eiji "Multistep Sequential Batch Assembly of Three-Dimensional Ferromagnetic Microstructures with Elastic Hinges", Retrieved at <<<http://ieeexplore.ieee.org/stamp/stamp.jsp?tp=&arnumber=1549861>>> Proceedings: Journal of Microelectromechanical Systems, (Dec. 2005), 7 pages.
 Valliath, G T., "Design of Hologram for Brightness Enhancement in Color LCDs", Retrieved from <http://www.loreti.it/Download/PDF/LCD/44_05.pdf> on Sep. 17, 2012, 5 pages.
 Williams, Jim "A Fourth Generation of LCD Backlight Technology", Retrieved from <<http://cds.linear.com/docs/Application%20Note/an65f.pdf>>, (Nov. 1995), 124 pages.
 Kaur, Sukhmani, "Vincent Liew's redesigned laptop satisfies ergonomic needs", Retrieved at <<<http://www.designbuzz.com/entry/vincent-liew-s-redesigned-laptop-satisfies-ergonomic-needs/>>>, Jun. 21, 2010, pp. 4.
 "Accessing Device Sensors", retrieved from <<https://developer.palm.com/content/api/dev-guide/pdk/accessing-device-sensors.html>> on May 25, 2012, 4 pages.
 "First One Handed Fabric Keyboard with Bluetooth Wireless Technology", Retrieved from: <<http://press.xtvworld.com/article3817.html>> on May 8, 2012, (Jan. 6, 2005), 2 pages.
 "Force and Position Sensing Resistors: An Emerging Technology", *Interlink Electronics*, Available at <http://staff.science.uva.nl/~vlaander/docu/FSR/An_Exploring_Technology.pdf>, (Feb. 1990), pp. 1-6.
 "Frogpad Introduces Wearable Fabric Keyboard with Bluetooth Technology", Retrieved from: <<http://www.geekzone.co.nz/content.asp?contentid=3898>> on May 7, 2012, (Jan. 7, 2005), 3 pages.
 "Incipio LG G-Slate Premium Kickstand Case—Black Nylon", Retrieved from: <<http://www.amazon.com/Incipio-G-Slate-Premium-Kickstand-Case/dp/B004ZKP916>> on May 8, 2012, 4 pages.
 "Membrane Keyboards & Membrane Keypads", Retrieved from: <<http://www.pannam.com/>> on May 9, 2012, (Mar. 4, 2009), 2 pages.
 "Motion Sensors", *Android Developers*, retrieved from <http://developer.android.com/guide/topics/sensors/sensors_motion.html> on May 25, 2012, 7 pages.
 "Position Sensors", *Android Developers*, retrieved from <http://developer.android.com/guide/topics/sensors/sensors_position.html> on May 25, 2012, 5 pages.

(56)

References Cited

OTHER PUBLICATIONS

- "SoIRx™ E-Series Multidirectional Phototherapy Expandable™ 2-Bulb Full Body Panel System", Retrieved from: < http://www.solarcsystems.com/us_multidirectional_uv_light_therapy_1_intro.html > on Jul. 25, 2012,(2011), 4 pages.
- "Virtualization Getting Started Guide", *Red Hat Enterprise Linux 6, Edition 0.2*, retrieved from <http://docs.redhat.com/docs/en-US/Red_Hat_Enterprise_Linux/6/html-single/Virtualization_Getting_Started_Guide/index.html> on Jun. 13, 2012, 24 pages.
- Block, Steve et al., "DeviceOrientation Event Specification", *W3C, Editor's Draft*, retrieved from <<https://developer.palm.com/content/api/dev-guide/pdk/accessing-device-sensors.html>> on May 25, 2012,(Jul. 12, 2011), 14 pages.
- Brown, Rich "Microsoft Shows Off Pressure-Sensitive Keyboard", retrieved from <http://news.cnet.com/8301-17938_105-10304792-1.html> on May 7, 2012, (Aug. 6, 2009), 2 pages.
- Butler, Alex et al., "SideSight: Multi-"touch" Interaction around Small Devices", *In the proceedings of the 21st annual ACM symposium on User interface software and technology*, retrieved from <http://research.microsoft.com/pubs/132534/sidesight_crv3.pdf> on May 29, 2012,(Oct. 19, 2008), 4 pages.
- Crider, Michael "Sony Slate Concept Tablet "Grows" a Kickstand", Retrieved from: <<http://androidcommunity.com/sony-slate-concept-tablet-grows-a-kickstand-20120116/>> on May 4, 2012,(Jan. 16, 2012), 9 pages.
- Dietz, Paul H., et al., "A Practical Pressure Sensitive Computer Keyboard", In Proceedings of UIST 2009,(Oct. 2009), 4 pages.
- Glatt, Jeff "Channel and Key Pressure (Aftertouch).", Retrieved from: <<http://home.roadrunner.com/~jgglatt/tutr/touch.htm>> on Jun. 11, 2012, 2 pages.
- Hanlon, Mike "ElekTex Smart Fabric Keyboard Goes Wireless", Retrieved from: <<http://www.gizmag.com/go/5048/>> on May 7, 2012,(Jan. 15, 2006), 5 pages.
- Khuntontong, Puttachat et al., "Fabrication of Molded Interconnection Devices by Ultrasonic Hot Embossing on Thin Polymer Films", *IEEE Transactions on Electronics Packaging Manufacturing*, vol. 32, No. 3,(Jul. 2009), pp. 152-156.
- Linderholm, Owen "Logitech Shows Cloth Keyboard for PDAs", Retrieved from: <http://www.pcworld.com/article/89084/logitech-shows_cloth_keyboard_for_pdas.html> on May 7, 2012,(Mar. 15, 2002), 5 pages.
- McLellan, Charles "Elekten Wireless Fabric Keyboard: a first look", Retrieved from: <<http://www.zdnetasia.com/elekten-wireless-fabric-keyboard-a-first-look-40278954.htm>> on May 7, 2012,(Jul. 17, 2006), 9 pages.
- Post, E.R. et al., "E-Broidery: Design and Fabrication of Textile-Based Computing", *IBM Systems Journal*, vol. 39, Issue 3 & 4,(Jul. 2000), pp. 840-860.
- Purcher, Jack "Apple is Paving the Way for a New 3D GUI for IOS Devices", Retrieved from: <<http://www.patentlyapple.com/patently-apple/2012/01/apple-is-paving-the-way-for-a-new-3d-gui-for-ios-devices.html>> on Jun. 4, 2012,(Jan. 12, 2012), 15 pages.
- Takamatsu, Seiichi et al., "Flexible Fabric Keyboard with Conductive Polymer-Coated Fibers", In Proceedings of Sensors 2011,(Oct. 28, 2011), 4 pages.
- Zhang, et al., "Model-Based Development of Dynamically Adaptive Software", In *Proceedings of ICSE 2006*, Available at <<http://www.irisa.fr/lande/lande/icse-proceedings/icse/p371.pdf>>,(May 20, 2006), pp. 371-380.
- "Cirago Slim Case®- Protective case with built-in kickstand for your iPhone 5®", Retrieved from <<http://cirago.com/wordpress/wp-content/uploads/2012/10/ipc1500brochure1.pdf>> on Jan. 29, 2013, (Jan. 2013), 1 page.
- "Non-Final Office Action", U.S. Appl. No. 13/471,001, (Feb. 19, 2013), 15 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/471,139, (Mar. 21, 2013), 12 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/471,202, (Feb. 11, 2013), 10 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/471,336, (Jan. 18, 2013), 14 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,195, (Jan. 2, 2013), 14 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,232, (Jan. 17, 2013), 15 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,272, (Feb. 12, 2013), 10 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,287, (Jan. 29, 2013), 13 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,304, (Mar. 22, 2013), 9 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,327, (Mar. 22, 2013), 6 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,871, (Mar. 18, 2013), 14 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,976, (Feb. 22, 2013), 16 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/653,321, (Feb. 1, 2013), 13 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/653,682, (Feb. 7, 2013), 11 pages.
- "Notice of Allowance", U.S. Appl. No. 13/470,633, (Mar. 22, 2013), 7 pages.
- "Restriction Requirement", U.S. Appl. No. 13/471,139, (Jan. 17, 2013), 7 pages.
- "Restriction Requirement", U.S. Appl. No. 13/651,304, (Jan. 18, 2013), 7 pages.
- "Restriction Requirement", U.S. Appl. No. 13/651,726, (Feb. 22, 2013), 6 pages.
- "Restriction Requirement", U.S. Appl. No. 13/651,871, (Feb. 7, 2013), 6 pages.
- "The Microsoft Surface Tablets Comes With Impressive Design and Specs", Retrieved from <<http://microsofttabletreview.com/the-microsoft-surface-tablets-comes-with-impressive-design-and-specs>> on Jan. 30, 2013, (Jun. 2012), 2 pages.
- "Tilt Shift Lenses: Perspective Control", retrieved from <http://www.cambridgeincolour.com/tutorials/tilt-shift-lenses1.htm>, (Mar. 28, 2008), 11 Pages.
- "What is Active Alignment?", http://www.kasalis.com/active_alignment.html, retrieved on Nov. 22, 2012, 2 Pages.
- "Corrected Notice of Allowance", U.S. Appl. No. 13/470,633, (Jul. 2, 2013), 2 pages.
- "Corrected Notice of Allowance", U.S. Appl. No. 13/651,327, (Sep. 12, 2013), 2 pages.
- "Corrected Notice of Allowance", U.S. Appl. No. 13/651,327, (Sep. 23, 2013), 2 pages.
- "Corrected Notice of Allowance", U.S. Appl. No. 13/651,726, (Sep. 17, 2013), 2 pages.
- "Final Office Action", U.S. Appl. No. 13/471,001, (Jul. 25, 2013), 20 pages.
- "Final Office Action", U.S. Appl. No. 13/471,139, (Sep. 16, 2013), 13 pages.
- "Final Office Action", U.S. Appl. No. 13/471,336, (Aug. 28, 2013), 18 pages.
- "Final Office Action", U.S. Appl. No. 13/651,976, (Jul. 25, 2013), 21 pages.
- "Final Office Action", U.S. Appl. No. 13/653,321, (Aug. 2, 2013), 17 pages.
- "Final Office Action", U.S. Appl. No. 13/653,682, (Oct. 18, 2013), 16 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/527,263, (Jul. 19, 2013), 5 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/564,520, (Jun. 19, 2013), 8 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/565,124, (Jun. 17, 2013), 5 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/651,871, (Jul. 1, 2013), 5 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/653,682, (Jun. 3, 2013), 14 pages.
- "Non-Final Office Action", U.S. Appl. No. 13/938,930, (Aug. 29, 2013), 9 pages.

(56)

References Cited

OTHER PUBLICATIONS

“Non-Final Office Action”, U.S. Appl. No. 13/939,002, (Aug. 28, 2013), 6 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/939,032, (Aug. 29, 2013), 7 pages.

“Notice of Allowance”, U.S. Appl. No. 13/651,195, (Jul. 8, 2013), 9 pages.

“Notice of Allowance”, U.S. Appl. No. 13/651,304, (Jul. 1, 2013), 5 pages.

“Notice of Allowance”, U.S. Appl. No. 13/651,327, (Jun. 11, 2013), 7 pages.

“Notice of Allowance”, U.S. Appl. No. 13/651,726, (May 31, 2013), 5 pages.

“Notice of Allowance”, U.S. Appl. No. 13/651,871, (Oct. 2, 2013), 7 pages.

“Notice to Grant”, Chinese Application No. 201320097089.9, (Sep. 29, 2013), 2 Pages.

“PCT Search Report and Written Opinion”, Application No. PCT/US2013/029461, (Jun. 21, 2013), 11 pages.

“PCT Search Report and Written Opinion”, Application No. PCT/US2013/028948, (Jun. 21, 2013), 11 pages.

“Advanced Configuration and Power Management Specification”, *Intel Corporation, Microsoft Corporation, Toshiba Corp. Revision 1*, (Dec. 22, 1996), 364 pages.

“Final Office Action”, U.S. Appl. No. 13/656,055, (Oct. 23, 2013), 14 pages.

“Final Office Action”, U.S. Appl. No. 13/938,930, (Nov. 8, 2013), 10 pages.

“Final Office Action”, U.S. Appl. No. 13/939,002, (Nov. 8, 2013), 7 pages.

“International Search Report and Written Opinion”, Application No. PCT/US2013/044871, (Aug. 14, 2013), 12 pages.

“International Search Report and Written Opinion”, Application No. PCT/US2013/045049, (Sep. 16, 2013), 9 pages.

“International Search Report and Written Opinion”, Application No. PCT/US2013/040968, (Sep. 5, 2013), 12 pages.

“International Search Report and Written Opinion”, Application No. PCT/US2013/042550, (Sep. 24, 2013), 14 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/371,725, (Nov. 7, 2013), 19 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/780,228, (Oct. 30, 2013), 12 pages.

“Notice of Allowance”, U.S. Appl. No. 13/656,520, (Oct. 2, 2013), 5 pages.

“Restriction Requirement”, U.S. Appl. No. 13/715,133, (Oct. 28, 2013), 6 pages.

“Restriction Requirement”, U.S. Appl. No. 13/715,229, (Aug. 13, 2013), 7 pages.

“Welcome to Windows 7”, Retrieved from: <<http://www.microsoft.com/en-us/download/confirmation.aspx?id=4984>> on Aug. 1, 2013, (Sep. 16, 2009), 3 pages.

“Write & Learn Spellboard Advanced”, Available at <<http://somemanuals.com/VTECH.WRITE%2526LEARN—Spellboard—ADV—71000,JIDFHE.PDF>>, (2006), 22 pages.

Bathiche, Steven N., et al., “Input Device with Interchangeable Surface”, U.S. Appl. No. 13/974,749, (Aug. 23, 2013), 51 pages.

Lance, David M., et al., “Media Processing Input Device”, U.S. Appl. No. 13/655,065, (Oct. 18, 2012), 43 pages.

Prospero, Michael “Samsung Outs Series 5 Hybrid PC Tablet”, Retrieved from: <<http://blog.laptopmag.com/samsung-outs-series-5-hybrid-pc-tablet-running-windows-8>> on Oct. 31, 2013, (Jun. 4, 2012), 7 pages.

“Final Office Action”, U.S. Appl. No. 13/939,032, Dec. 20, 2013, 5 pages.

“FingerWorks Installation and Operation Guide for the TouchStream ST and TouchStream LP”, FingerWorks, Inc. Retrieved from <<http://ec1.images-amazon.com/media/i3d/01/A/man-migrate/MANUAL000049862.pdf>>, 2002, 14 pages.

“Non-Final Office Action”, U.S. Appl. No. 14/063,912, Jan. 2, 2014, 10 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/651,232, Dec. 5, 2013, 15 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/468,918, Dec. 26, 2013, 18 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/939,002, Dec. 20, 2013, 5 pages.

“Non-Final Office Action”, U.S. Appl. No. 13/021,448, Dec. 13, 2012, 9 pages.

“Notice of Allowance”, U.S. Appl. No. 13/653,321, Dec. 18, 2013, 41 pages.

“Notice of Allowance”, U.S. Appl. No. 13/565,124, Dec. 24, 2013, 6 pages.

“Notice to Grant”, CN Application No. 201320097124.7, Oct. 8, 2013, 2 pages.

“Restriction Requirement”, U.S. Appl. No. 13/468,918, Nov. 29, 2013, 6 pages.

“Final Office Action”, U.S. Appl. No. 13/564,520, Jan. 15, 2014, 7 pages.




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10






Fig. 11

*Fig. 12**Fig. 13*




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20





Fig. 21

2200

*Fig. 22*

FLEXIBLE HINGE SPINE

This application claims priority as a continuation under 35 U.S.C. §120 to U.S. patent application Ser. No. 13/470,633, filed May 14, 2012, and titled "Flexible Hinge and Removable Attachment," the entire disclosure of which is hereby incorporated by reference, which claims priority under 35 U.S.C. §119(e) to the following U.S. Provisional patent applications, the entire disclosures of each of these applications being incorporated by reference in their entirety:

U.S. Provisional Patent Application No. 61/606,321, filed Mar. 2, 2012, and titled "Screen Edge;"

U.S. Provisional Patent Application No. 61/606,301, filed Mar. 2, 2012, and titled "Input Device Functionality;"

U.S. Provisional Patent Application No. 61/606,313, filed Mar. 2, 2012, and titled "Functional Hinge;"

U.S. Provisional Patent Application No. 61/606,333, filed Mar. 2, 2012, and titled "Usage and Authentication;"

U.S. Provisional Patent Application No. 61/613,745, filed Mar. 21, 2012, and titled "Usage and Authentication;"

U.S. Provisional Patent Application No. 61/606,336, filed Mar. 2, 2012, and titled "Kickstand and Camera;" and

U.S. Provisional Patent Application No. 61/607,451, filed Mar. 6, 2012, and titled "Spanaway Provisional;"

and further this application incorporates the following application by reference in its entirety, U.S. patent application Ser. No. 13/471,282, filed May 14, 2012, and titled "Input Device Assembly."

BACKGROUND

Mobile computing devices have been developed to increase the functionality that is made available to users in a mobile setting. For example, a user may interact with a mobile phone, tablet computer, or other mobile computing device to check email, surf the web, compose texts, interact with applications, and so on.

Because mobile computing devices are configured to be mobile, however, the devices may be exposed to a wide variety of environments having varying degrees of safety for the computing device. Accordingly, devices were developed to help protect the mobile computing devices from their environment. However, conventional techniques to install and remove the devices from the computing device alternated between being difficult to remove but providing good protection or being relatively easy to remove but providing limited protection.

SUMMARY

Flexible hinge and removable attachment techniques are described. In one or more implementations, a flexible hinge is configured to communicatively and physically couple an input device to a computing device. The flexible hinge may be configured to support movement of the input device similar to a cover of a book, such that the input device may act as a cover. Flexibility of the hinge may be implemented using a variety of techniques, such as a support layer to add strength to the device to protect components from repeated connection and removal from the computing device, e.g., conductors used for communication.

The hinge may also be configured to provide a minimum bend radius to further protect these conductors and other components. A variety of different techniques may be employed, such as use of embossing, a mid-spine, material choice, and so on. Additionally, techniques may be leveraged to provide mechanical stiffness to a connection portion that is

used to connect the input device to the computing device, such as to form a laminate structure through the use of pins.

The input device may also include functionality to promote a secure physical connection between the input device and the computing device. One example of this includes use of one or more protrusions that are configured to be removed from respective cavities of the computing device along a particular axis but mechanically bind along other axes. These protrusions may also be used for a variety of other purposes, such as to transmit power or communications between the devices.

This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

The detailed description is described with reference to the accompanying figures. In the figures, the left-most digit(s) of a reference number identifies the figure in which the reference number first appears. The use of the same reference numbers in different instances in the description and the figures may indicate similar or identical items. Entities represented in the figures may be indicative of one or more entities and thus reference may be made interchangeably to single or plural forms of the entities in the discussion.

FIG. 1 is an illustration of an environment in an example implementation that is operable to employ the techniques described herein.

FIG. 2 depicts an example implementation of an input device of FIG. 1 as showing a flexible hinge in greater detail.

FIG. 3 depicts an example orientation of the input device in relation to the computing device as covering a display device of the computing device.

FIG. 4 depicts an example orientation of the input device in relation to the computing device as assuming a typing orientation.

FIG. 5 depicts an example orientation of the input device in relation to the computing device as covering a rear housing of the computing device and exposing a display device of the computing device.

FIG. 6 depicts an example orientation of the input device as including a portion configured to cover a rear of the computing device, which in this instance is used to support a kickstand of the computing device.

FIG. 7 depicts an example orientation in which the input device including the portion of FIG. 6 are used to cover both the front and back of the computing device.

FIG. 8 depicts an example implementation showing a perspective view of a connection portion of FIG. 2 that includes mechanical coupling protrusions and a plurality of communication contacts.

FIG. 9 depicts a cross section taken along an axis showing a communication contact as well as a cross section of a cavity of the computing device in greater detail.

FIG. 10 depicts a cross section of the computing device, connection portion, and flexible hinge of the input device as being oriented as shown in FIG. 3 in which the input device acts as a cover for a display device of the computing device.

FIG. 11 depicts a cross section taken along an axis showing a magnetic coupling device as well as a cross section of the cavity of the computing device in greater detail.

FIG. 12 depicts an example of a magnetic coupling portion that may be employed by the input device or computing device to implement a flux fountain.

3

FIG. 13 depicts another example of a magnetic coupling portion that may be employed by the input device or computing device to implement a flux fountain.

FIG. 14 depicts a cross section taken along an axis showing a mechanical coupling protrusion as well as a cross section of the cavity of the computing device in greater detail.

FIG. 15 depicts a perspective view of a protrusion as configured to communicate signals and/or transmit power between the input device and the computing device.

FIG. 16 illustrates a top view of a protrusion in which a surface is divided to support a plurality of different contacts.

FIG. 17 depicts a cross section view of the protrusion of FIG. 16 as disposed within a cavity of the computing device.

FIG. 18 depicts an example implementation showing a support layer that is configured to support operation of the flexible hinge as well as protect components of the input device during this operation.

FIG. 19 depicts an example implementation in which a top view of the connection portion is shown.

FIG. 20 depicts a cross section view of the connection portion of FIG. 19.

FIG. 21 depicts an example cross sectional view of a first pin of FIG. 20 as securing a metal spine to plastic of the connection portion to form a laminate structure.

FIG. 22 illustrates an example system including various components of an example device that can be implemented as any type of computing device as described with reference to FIGS. 1-21 to implement embodiments of the techniques described herein.

DETAILED DESCRIPTION

Overview

A variety of different devices may be physically attached to a mobile computing device to provide a variety of functionality. For example, a device may be configured to provide a cover for at least a display device of the computing device to protect it against harm. Other devices may also be physically attached to the mobile computing device, such as an input device (e.g., keyboard having a track pad) to provide inputs to the computing device. Further, functionality of these devices may be combined, such as to provide a combination cover and input device. However, conventional techniques that were utilized to attach devices to the computing device may alternate between significant protection and corresponding complications in installing and removing the device to limited protection but having relative ease of installation and removal.

Techniques are described herein to removably and/or flexibly connect an input device or other device (e.g., a cover) with a computing device. These techniques include use of a flexible hinge to promote rotational movement similar to that of a book. Techniques may also be employed to protect components of the input device during this movement, such as to support a minimum bend radius to protect conductors of the input device from the flexible movement. These techniques may include material selection, use of a mid-spine, a support layer, and so on.

Techniques are also described to promote a secure physical coupling between the input device and the computing device. This may include use of one or more protrusions that are configured to be engaged in respective cavities of the computing device, or vice versa. The protrusions are configured to mechanically bind within the cavities when the input device is “pulled away” from the computing device along one or more axes, but permit removal along a particular axis. In this way,

4

the input device may have a secure connection through a wide range of movement yet still support ease of removal.

Techniques are also described to promote mechanical stiffness of a connection portion that is to be used to connect the input device to the computing device. The connection portion, for instance, may include a projection formed of plastic to be disposed within a channel of the computing device, or vice versa. A spine, such as a strip of metal (e.g., aluminum), may be secured to the projection to increase the mechanical stiffness. This securing may be performed through use of a plurality of pins such that a combination of the pins, spine, and projection may form a laminate structure having increased stiffness along an axis of the spine. Further, the pins may be used to support a variety of other functionality, such as to attach the spine to the projection while an adhesive (e.g., an epoxy) sets, thereby supporting a fast production cycle time that is not limited by the amount of time used to have the adhesive set. Once set, a combination of the adhesive and the pins may further promote mechanical stiffness of the connection portion. Further discussion of these and other techniques may be found in relation to the following sections.

In the following discussion, an example environment is first described that may employ the techniques described herein. Example procedures are then described which may be performed in the example environment as well as other environments. Consequently, performance of the example procedures is not limited to the example environment and the example environment is not limited to performance of the example procedures. Further, although an input device is described, other devices are also contemplated that do not include input functionality, such as covers. For example, these techniques are equally applicable to passive devices, e.g., a cover having one or more materials (e.g., magnets, ferrous material, and so on) that are configured and positioned within the cover to be attracted to magnetic coupling devices of the computing device, use of protrusions and connecting portion, and so on as further described below.

Example Environment

FIG. 1 is an illustration of an environment 100 in an example implementation that is operable to employ the techniques described herein. The illustrated environment 100 includes an example of a computing device 102 that is physically and communicatively coupled to an input device 104 via a flexible hinge 106. The computing device 102 may be configured in a variety of ways. For example, the computing device 102 may be configured for mobile use, such as a mobile phone, a tablet computer as illustrated, and so on. Thus, the computing device 102 may range from full resource devices with substantial memory and processor resources to a low-resource device with limited memory and/or processing resources. The computing device 102 may also relate to software that causes the computing device 102 to perform one or more operations.

The computing device 102, for instance, is illustrated as including an input/output module 108. The input/output module 108 is representative of functionality relating to processing of inputs and rendering outputs of the computing device 102. A variety of different inputs may be processed by the input/output module 108, such as inputs relating to functions that correspond to keys of the input device 104, keys of a virtual keyboard displayed by the display device 110 to identify gestures and cause operations to be performed that correspond to the gestures that may be recognized through the input device 104 and/or touchscreen functionality of the display device 110, and so forth. Thus, the input/output module 108 may support a variety of different input techniques by

5

recognizing and leveraging a division between types of inputs including key presses, gestures, and so on.

In the illustrated example, the input device **104** is configured as having an input portion that includes a keyboard having a QWERTY arrangement of keys and track pad although other arrangements of keys are also contemplated. Further, other non-conventional configurations are also contemplated, such as a game controller, configuration to mimic a musical instrument, and so forth. Thus, the input device **104** and keys incorporated by the input device **104** may assume a variety of different configurations to support a variety of different functionality.

As previously described, the input device **104** is physically and communicatively coupled to the computing device **102** in this example through use of a flexible hinge **106**. The flexible hinge **106** is flexible in that rotational movement supported by the hinge is achieved through flexing (e.g., bending) of the material forming the hinge as opposed to mechanical rotation as supported by a pin, although that embodiment is also contemplated. Further, this flexible rotation may be configured to support movement in one or more directions (e.g., vertically in the figure) yet restrict movement in other directions, such as lateral movement of the input device **104** in relation to the computing device **102**. This may be used to support consistent alignment of the input device **104** in relation to the computing device **102**, such as to align sensors used to change power states, application states, and so on.

The flexible hinge **106**, for instance, may be formed using one or more layers of fabric and include conductors formed as flexible traces to communicatively couple the input device **104** to the computing device **102** and vice versa. This communication, for instance, may be used to communicate a result of a key press to the computing device **102**, receive power from the computing device, perform authentication, provide supplemental power to the computing device **102**, and so on. The flexible hinge **106** may be configured in a variety of ways, further discussion of which may be found in relation to the following figure.

FIG. 2 depicts an example implementation **200** of the input device **104** of FIG. 1 as showing the flexible hinge **106** in greater detail. In this example, a connection portion **202** of the input device is shown that is configured to provide a communicative and physical connection between the input device **104** and the computing device **102**. The connection portion **202** as illustrated has a height and cross section configured to be received in a channel in the housing of the computing device **102**, although this arrangement may also be reversed without departing from the spirit and scope thereof.

The connection portion **202** is flexibly connected to a portion of the input device **104** that includes the keys through use of the flexible hinge **106**. Thus, when the connection portion **202** is physically connected to the computing device the combination of the connection portion **202** and the flexible hinge **106** supports movement of the input device **104** in relation to the computing device **102** that is similar to a hinge of a book.

Through this rotational movement, a variety of different orientations of the input device **104** in relation to the computing device **102** may be supported. For example, rotational movement may be supported by the flexible hinge **106** such that the input device **104** may be placed against the display device **110** of the computing device **102** and thereby act as a cover as shown in the example orientation **300** of FIG. 3. Thus, the input device **104** may act to protect the display device **110** of the computing device **102** from harm.

As shown in the example orientation **400** of FIG. 4, a typing arrangement may be supported. In this orientation, the input

6

device **104** is laid flat against a surface and the computing device **102** is disposed at an angle to permit viewing of the display device **110**, e.g., such as through use of a kickstand **402** disposed on a rear surface of the computing device **102**.

In the example orientation **500** of FIG. 5, the input device **104** may also be rotated so as to be disposed against a back of the computing device **102**, e.g., against a rear housing of the computing device **102** that is disposed opposite the display device **110** on the computing device **102**. In this example, through orientation of the connection portion **202** to the computing device **102**, the flexible hinge **106** is caused to “wrap around” the connection portion **202** to position the input device **104** at the rear of the computing device **102**.

This wrapping causes a portion of a rear of the computing device **102** to remain exposed. This may be leveraged for a variety of functionality, such as to permit a camera **502** positioned on the rear of the computing device **102** to be used even though a significant portion of the rear of the computing device **102** is covered by the input device **104** in this example orientation **500**. Although configuration of the input device **104** to cover a single side of the computing device **102** at any one time was described above, other configurations are also contemplated.

In the example orientation **600** of FIG. 6, the input device **104** is illustrated as including a portion **602** configured to cover a rear of the computing device. This portion **602** is also connected to the connection portion **202** using a flexible hinge **604**.

The example orientation **600** of FIG. 6 also illustrates a typing arrangement in which the input device **104** is laid flat against a surface and the computing device **102** is disposed at an angle to permit viewing of the display device **110**. This is supported through use of a kickstand **402** disposed on a rear surface of the computing device **102** to contact the portion **602** in this example.

FIG. 7 depicts an example orientation **700** in which the input device **104** including the portion **602** are used to cover both the front (e.g., display device **110**) and back (e.g., opposing side of the housing from the display device) of the computing device **102**. In one or more implementations, electrical and other connectors may also be disposed along the sides of the computing device **102** and/or the input device **104**, e.g., to provide auxiliary power when closed.

Naturally, a variety of other orientations are also supported. For instance, the computing device **102** and input device **104** may assume an arrangement such that both are laid flat against a surface as shown in FIG. 1. Other instances are also contemplated, such as a tripod arrangement, meeting arrangement, presentation arrangement, and so forth.

Returning again to FIG. 2, the connection portion **202** is illustrated in this example as including magnetic coupling devices **204**, **206**, mechanical coupling protrusions **208**, **210**, and a plurality of communication contacts **212**. The magnetic coupling devices **204**, **206** are configured to magnetically couple to complementary magnetic coupling devices of the computing device **102** through use of one or more magnets. In this way, the input device **104** may be physically secured to the computing device **102** through use of magnetic attraction.

The connection portion **202** also includes mechanical coupling protrusions **208**, **210** to form a mechanical physical connection between the input device **104** and the computing device **102**. The mechanical coupling protrusions **208**, **210** are shown in greater detail in relation to FIG. 8, which is discussed below.

FIG. 8 depicts an example implementation **800** showing a perspective view of the connection portion **202** of FIG. 2 that includes the mechanical coupling protrusions **208**, **210** and

the plurality of communication contacts **212**. As illustrated, the mechanical coupling protrusions **208**, **210** are configured to extend away from a surface of the connection portion **202**, which in this case is perpendicular although other angles are also contemplated.

The mechanical coupling protrusions **208**, **210** are configured to be received within complimentary cavities within the channel of the computing device **102**. When so received, the mechanical coupling protrusions **208**, **210** promote a mechanical binding between the devices when forces are applied that are not aligned with an axis that is defined as correspond to the height of the protrusions and the depth of the cavity, further discussion of which may be found in relation to FIG. **14**.

The connection portion **202** is also illustrated as including a plurality of communication contacts **212**. The plurality of communication contacts **212** is configured to contact corresponding communication contacts of the computing device **102** to form a communicative coupling between the devices as shown and discussed in greater detail in relation to the following figure.

FIG. **9** depicts a cross section taken along an axis **900** of FIGS. **2** and **8** showing one of the communication contacts **212** as well as a cross section of a cavity of the computing device **102** in greater detail. The connection portion **202** is illustrated as including a projection **902** that is configured to be complimentary to a channel **904** of the computing device **102**, e.g., having complimentary shapes, such that movement of the projection **902** within the cavity **904** is limited.

The communication contacts **212** may be configured in a variety of ways. In the illustrated example, the communication contact **212** of the connection portion **202** is formed as a spring loaded pin **906** that is captured within a barrel **908** of the connection portion **202**. The spring loaded pin **906** is biased outward from the barrel **908** to provide a consistent communication contact between the input device **104** and the computing device **102**, such as to a contact **910** of the computing device **102**. Therefore, contact and therefore communication may be maintained during movement or jostling of the devices. A variety of other examples are also contemplated, including placement of the pins on the computing device **102** and contacts on the input device **104**.

The flexible hinge **106** is also shown in greater detail in the example of FIG. **9**. The flexible hinge **106** in this cross section includes a conductor **912** that is configured to communicatively coupled the communication contact **212** of the connection portion **202** with an input portion **914** of the input device **104**, e.g., one or more keys, a track pad, and so forth. The conductor **912** may be formed in a variety of ways, such as a copper trace that has an operational flexibility to permit operation as part of the flexible hinge, e.g., to support repeated flexing of the hinge **106**. Flexibility of the conductor **912**, however, may be limited, e.g., may remain operational to conduct signals for flexing that is performed above a minimum bend radius.

Accordingly, the flexible hinge **106** may be configured to support a minimum bend radius based on the operational flexibility of the conductor **912** such that the flexible hinge **106** resists flexing below that radius. A variety of different techniques may be employed. The flexible hinge **106**, for instance, may be configured to include first and second outer layers **916**, **918**, which may be formed from a fabric, microfiber cloth, and so on. Flexibility of material used to form the first and/or second outer layers **916**, **918** may be configured to support flexibility as described above such that the conductor

912 is not broken or otherwise rendered inoperable during movement of the input portion **914** in relation to the connection portion **202**.

In another instance, the flexible hinge **106** may include a mid-spine **920** located between the connection portion **202** and the input portion **914**. The mid-spine **920**, for example, includes a first flexible portion **922** that flexible connects the input portion **904** to the mid-spine **920** and a second flexible portion **924** that flexible connects the mid-spine **920** to the connection portion **202**.

In the illustrated example, the first and second outer layers **916**, **918** extend from the input portion **914** (and act as a cover thereof) through the first and second flexible portions **922**, **924** of the flexible hinge **106** and are secured to the connection portion **202**, e.g., via clamping, adhesive, and so on. The conductor **912** is disposed between the first and second outer layers **916**, **918**. The mid-spine **920** may be configured to provide mechanical stiffness to a particular location of the flexible hinge **106** to support a desired minimum bend radius, further discussion of which may be found in relation to the following figure.

FIG. **10** depicts a cross section of the computing device **102**, connection portion **202** and flexible hinge **106** of the input device **104** as being oriented as shown in FIG. **3** in which the input device **104** acts as a cover for a display device **110** of the computing device **102**. As illustrated, this orientation causes the flexible hinge **106** to bend. Through inclusion of the mid-spine **920** and sizing of the first and second flexible portions **922**, **924**, however, the bend does not exceed an operational bend radius of the conductor **912** as previously described. In this way, the mechanical stiffness provided by the mid-spine **920** (which is greater than a mechanical stiffness of other portions of the flexible hinge **106**) may protect the conductors **912**.

The mid-spine **920** may also be used to support a variety of other functionality. For example, the mid-spine **920** may support movement along a longitudinal axis as shown in FIG. **1** yet help restrict movement along a latitudinal axis that otherwise may be encountered due to the flexibility of the flexible hinge **106**.

Other techniques may also be leveraged to provide desired flexibility at particular points along the flexible hinge **106**. For example, embossing may be used in which an embossed area, e.g., an area that mimics a size and orientation of the mid-spine **920**, is configured to increase flexibility of a material, such as one or more of the first and second outer layers **916**, **918**, at locations that are embossed. An example of an embossed line **214** that increases flexibility of a material along a particular axis is shown in FIG. **2**. It should be readily apparent, however, that a wide variety of shapes, depths, and orientations of an embossed area are also contemplated to provide desired flexibility of the flexible hinge **106**.

FIG. **11** depicts a cross section taken along an axis **1100** of FIGS. **2** and **8** showing the magnetic coupling device **204** as well as a cross section of the cavity **904** of the computing device **102** in greater detail. In this example, a magnet of the magnetic coupling device **204** is illustrated as disposed within the connection portion **202**.

Movement of the connection portion **202** and the channel **904** together may cause the magnet **1102** to be attracted to a magnet **1104** of a magnetic coupling device **1106** of the computing device **102**, which in this example is disposed within the channel **904** of a housing of the computing device **102**. In one or more implementations, flexibility of the flexible hinge **106** may cause the connection portion **202** to “snap into” the channel **904**. Further, this may also cause the connection portion **202** to “line up” with the channel **904**, such

that the mechanical coupling protrusion **208** is aligned for insertion into the cavity **1002** and the communication contacts **208** are aligned with respective contacts **910** in the channel.

The magnetic coupling devices **204**, **1106** may be configured in a variety of ways. For example, the magnetic coupling device **204** may employ a backing **1108** (e.g., such as steel) to cause a magnetic field generated by the magnet **1102** to extend outward away from the backing **1108**. Thus, a range of the magnetic field generated by the magnet **1102** may be extended. A variety of other configurations may also be employed by the magnetic coupling device **204**, **1106**, examples of which are described and shown in relation to the following referenced figure.

FIG. **12** depicts an example **1200** of a magnetic coupling portion that may be employed by the input device **104** or computing device **102** to implement a flux fountain. In this example, alignment of a magnet field is indicted for each of a plurality of magnets using arrows.

A first magnet **1202** is disposed in the magnetic coupling device having a magnetic field aligned along an axis. Second and third magnets **1204**, **1206** are disposed on opposing sides of the first magnet **1202**. The alignment of the respective magnetic fields of the second and third magnets **1204**, **1206** is substantially perpendicular to the axis of the first magnet **1202** and generally opposed each other.

In this case, the magnetic fields of the second and third magnets are aimed towards the first magnet **1202**. This causes the magnetic field of the first magnet **1202** to extend further along the indicated axis, thereby increasing a range of the magnetic field of the first magnet **1202**.

The effect may be further extended using fourth and fifth magnets **1208**, **1210**. In this example, the fourth and fifth magnets **1208**, **1210** have magnetic fields that are aligned as substantially opposite to the magnetic field of the first magnet **1202**. Further, the second magnet **1204** is disposed between the fourth magnet **1208** and the first magnet **1202**. The third magnet **1206** is disposed between the first magnet **1202** and the fifth magnet **1210**. Thus, the magnetic fields of the fourth and fifth magnets **1208**, **1210** may also be caused to extend further along their respective axes which may further increase the strength of these magnets as well as other magnets in the collection. This arrangement of five magnets is suitable to form a flux fountain. Although five magnets were described, any odd number of magnets of five and greater may repeat this relationship to form flux fountains of even greater strength.

To magnetically attach to another magnetic coupling device, a similar arrangement of magnets may be disposed “on top” or “below” of the illustrated arrangement, e.g., so the magnetic fields of the first, fourth and fifth magnets **1202**, **1208**, **1210** are aligned with corresponding magnets above or below those magnets. Further, in the illustrated example, the strength of the first, fourth, and fifth magnets **1202**, **1208**, **1210** is stronger than the second and third magnets **1204**, **1206**, although other implementations are also contemplated. Another example of a flux fountain is described in relation to the following discussion of the figure.

FIG. **13** depicts an example **1300** of a magnetic coupling portion that may be employed by the input device **104** or computing device **102** to implement a flux fountain. In this example, alignment of a magnet field is also indicted for each of a plurality of magnets using arrows.

Like the example **1200** of FIG. **12**, a first magnet **1302** is disposed in the magnetic coupling device having a magnetic field aligned along an axis. Second and third magnets **1304**, **1306** are disposed on opposing sides of the first magnet **1302**. The alignment of the magnetic fields of the second and third

magnets **1304**, **1306** are substantially perpendicular the axis of the first magnet **1302** and generally opposed each other like the example **1200** of FIG. **12**.

In this case, the magnetic fields of the second and third magnets are aimed towards the first magnet **1302**. This causes the magnetic field of the first magnet **1302** to extend further along the indicated axis, thereby increasing a range of the magnetic field of the first magnet **1302**.

This effect may be further extended using fourth and fifth magnets **1308**, **1310**. In this example, the fourth magnet **1308** has a magnetic field that is aligned as substantially opposite to the magnetic field of the first magnet **1302**. The fifth magnet **1310** has a magnetic field that is aligned as substantially corresponding to the magnet field of the second magnet **1304** and is substantially opposite to the magnetic field of the third magnet **1306**. The fourth magnet **1308** is disposed between the third and fifth magnets **1306**, **1310** in the magnetic coupling device.

This arrangement of five magnets is suitable to form a flux fountain. Although five magnets are described, any odd number of magnets of five and greater may repeat this relationship to form flux fountains of even greater strength. Thus, the magnetic fields of the first **1302** and fourth magnet **1308** may also be caused to extend further along its axis which may further increase the strength of this magnet.

To magnetically attach to another magnetic coupling device, a similar arrangement of magnets may be disposed “on top” or “below” of the illustrated arrangement, e.g., so the magnetic fields of the first and fourth magnets **1302**, **1308** are aligned with corresponding magnets above or below those magnets. Further, in the illustrated example, the strength of the first and fourth magnets **1302**, **1308** (individually) is stronger than a strength of the second, third and fifth magnets **1304**, **1306**, **1310**, although other implementations are also contemplated.

Further, the example **1200** of FIG. **12**, using similar sizes of magnets, may have increased magnetic coupling as opposed to the example **1300** of FIG. **13**. For instance, the example **1200** of FIG. **12** uses three magnets (e.g. the first, fourth, and fifth magnets **1202**, **1208**, **1210**) to primarily provide the magnetic coupling, with two magnets used to “steer” the magnetic fields of those magnets, e.g., the second and third magnets **1204**, **1206**. However, the example **1300** of FIG. **13** uses two magnets (e.g., the first and fourth magnets **1302**, **1308**) to primarily provide the magnetic coupling, with three magnets used to “steer” the magnetic fields of those magnets, e.g., the second, third, and fifth magnets **1304**, **1306**, **1308**.

Accordingly, though, the example **1300** of FIG. **13**, using similar sizes of magnets, may have increased magnetic alignment capabilities as opposed to the example **1200** of FIG. **12**. For instance, the example **1300** of FIG. **13** uses three magnets (e.g. the second, third, and fifth magnets **1304**, **1306**, **1310**) to “steer” the magnetic fields of the first and fourth magnets **1302**, **1308**, which are used to provide primary magnetic coupling. Therefore, the alignment of the fields of the magnets in the example **1300** of FIG. **13** may be closer than the alignment of the example **1200** of FIG. **12**.

Regardless of the technique employed, it should be readily apparent that the “steering” or “aiming” of the magnetic fields described may be used to increase an effective range of the magnets, e.g., in comparison with the use of the magnets having similar strengths by themselves in a conventional aligned state. In one or more implementations, this causes an increase from a few millimeters using an amount of magnetic material to a few centimeters using the same amount of magnetic material.

11

FIG. 14 depicts a cross section taken along an axis 1400 of FIGS. 2 and 8 showing the mechanical coupling protrusion 208 as well as a cross section of the cavity 904 of the computing device 102 in greater detail. As before, the projection 902 and channel 904 are configured to have complementary sizes and shapes to limit movement of the connection portion 202 with respect to the computing device 102.

In this example, the projection 902 of the connection portion 202 also includes disposed thereon the mechanical coupling protrusion 208 that is configured to be received in a complementary cavity 1402 disposed within the channel 904. The cavity 1402, for instance, may be configured to receive the protrusion 1002 when configured as a substantially oval post as shown in FIG. 8, although other examples are also contemplated.

When a force is applied that coincides with a longitudinal axis that follows the height of the mechanical coupling protrusion 208 and the depth of the cavity 1002, a user overcomes the magnetic coupling force applied by the magnets solely to separate the input device 104 from the computing device 102. However, when a force is applied along another axis (i.e., at other angles) the mechanical coupling protrusion 208 is configured to mechanically bind within the cavity 1002. This creates a mechanical force to resist removal of the input device 104 from the computing device 102 in addition to the magnetic force of the magnetic coupling devices 204, 206.

In this way, the mechanical coupling protrusion 208 may bias the removal of the input device 104 from the computing device 102 to mimic tearing a page from a book and restrict other attempts to separate the devices. Referring again to FIG. 1, a user may grasp the input device 104 with one hand and the computing device 102 with another and pull the devices generally away from each other while in this relatively "flat" orientation. Through bending of the flexible hinge 106 the protrusion 208 and an axis of the cavity 1402 may be generally aligned to permit removal.

However, at other orientations, such as those shown in FIGS. 3-7, sides of the protrusion 208 may bind against sides of the cavity 1402, thereby restricting removal and promoting a secure connection between the devices. The protrusion 208 and cavity 1402 may be oriented in relation to each other in a variety of other ways as described to promote removal along a desired axis and promote a secure connection along other axes without departing from the spirit and scope thereof. The protrusion 208 may also be leveraged to provide a variety of other functionality besides mechanical retention, examples of which are discussed in relation to the following figures.

FIG. 15 depicts a perspective view 1500 of the protrusion as configured to communicate signals and/or transmit power between the input device 104 and the computing device 102. In this example, a top surface 1502 of the protrusion is configured to communicatively connect with a contact disposed within a cavity 1402 of the computing device 1402, or vice versa.

This contact may be used for a variety of purposes, such as to transmit power from the computing device 102 to the input device 104, from auxiliary power of the input device 104 to the computing device, communicate signals (e.g., signals generated from the keys of the keyboard), and so forth. Further, as shown in the top view 1600 of FIG. 16, the surface 1502 may be divided to support a plurality of different contacts, such as first and second contacts 1602, 1604 although other numbers, shapes, and sizes are also contemplated.

FIG. 17 depicts a cross section view 1700 of the protrusion 208 of FIG. 16 as disposed within the cavity 1402 of the computing device 102. In this example, first and second contacts 1702, 1704 include spring features to bias the contacts

12

outward from the cavity 1402. The first and second contacts 1702, 1704 are configured to contact the first and second contacts 1602, 1602 of the protrusion, respectively. Further, the first contact 1702 is configured as a ground that is configured to contact the first contact 1602 of the protrusion 208 before the second contact 1704 touches the second contact 1604 of the protrusion 208. In this way, the input device 104 and the computing device 102 may be protected against electrical shorts. A variety of other examples are also contemplated without departing from the spirit and scope thereof.

FIG. 18 depicts an example implementation 1800 showing a support layer 1802 that is configured to support operation of the flexible hinge 106 as well as protect components of the input device 104 during this operation. As shown in relation to FIGS. 3-7, the flexible hinge 106 may be configured to support various degrees of bending to assume the different configurations.

However, materials chosen to form the flexible hinge 106, such as to form the first and second outer layers 916, 918 of the flexible hinge 106 may be chosen to support a desired "look and feel" and therefore may not provide desired resiliency against tearing and stretching. Therefore, in such an instance this could have an effect on operability of the conductors 912. For example, as previously described a user may grasp the input device 104 with one hand to pull it away from the computing device 102 by disengaging the protrusions 208 and magnetic attraction supported by the magnets. Therefore, this could result in an amount of force being applied to the conductors that is sufficient to break them absent sufficient support from the first or second outer surfaces 916, 918 or other structure.

Accordingly, the input device 104 may include a support layer 804 that may be configured to protect the flexible hinge 106 and other components of the input device 104. For example, the support layer 804 may be formed of a material that has a higher resistance to tearing and stretching than a material used to form the first or second outer layers 916, 918, e.g., biaxially-oriented polyethylene terephthalate (BoPET) which is also known as Mylar.

Support provided by the support layer 1802 may thus help protect the material used to form the first and second outer surfaces 916, 918 of the flexible hinge 106. The support layer 1802 may also help protect components disposed through the hinge, such as the conductors 912 used to communicatively couple the connection portion 202 with the keys.

In the illustrated example, the support layer 1802 includes a portion 1804 configured to be disposed as part of the input portion 914 of the input device 104 that includes the keys, track pad, and so on as shown in FIG. 1. The support layer 1802 also includes first and second tabs 1806, 1808 that are configured to extend from the portion 1804 through the flexible hinge 106 to be secured to the connection portion 202. The tabs may be secured in a variety of ways, such as to include one or more holes as illustrated through which a protrusion (e.g., screw, pin, and so on) may be inserted to secure the tabs to the connection portion 202.

The first and second tabs 1806, 1808 are illustrated in this example as being configured to connect at approximate opposing ends of the connection portion 202. In this way, undesirable rotational movement may be restricted, e.g., that is perpendicular to a longitudinal axis defined by the connection portion 202. Thus, the conductors 912 disposed at a relative midpoint of the flexible hinge 106 and connection portion 202 may also be protected from tearing, stretching, and other forces.

The support layer 1802 in this illustrated example also includes a mid-spine portion 18010 that is configured to form

13

part of the mid-spine **920** that is described in relation to FIGS. **9** and **10**. Thus, the support layer **1802** may also act to increase the mechanical stiffness of the mid-spine **920** and contribute to the minimum bend radius as also previously described. Although first and second tabs **1806**, **1808** are illustrated, it should be readily apparent that more or fewer tabs may also be employed by the support layer **1802** to support the functionality described.

FIG. **19** depicts an example implementation **1900** in which a top view of the connection portion **202** is shown. The connection portion **202** may be configured in a variety of ways and from a variety of materials, such as metals, plastics, and so on. These different materials may be chosen based on desired functionality.

For example, a designer may desire ease of insertion and removal of the connection portion **202** from the cavity of the computing device **102** and accordingly select a material that is smooth and that has a relatively high resistance to wear. However, such a material may not provide a desired resistance to flexing, which could cause inconsistent contact between portions of the connection portion **202** with the computing device **102**. Accordingly, a designer may choose to utilize a plurality of pins at first, second, third, and fourth locations **1902**, **1904**, **1906**, and **1908** along a longitudinal axis of the connection portion **202** to provide the desired stiffness.

FIG. **20** depicts a cross section view **2000** of the connection portion **202** of FIG. **19**. As illustrated, first, second, third, and fourth pins **2002**, **2004**, **2006**, **2008** are utilized to secure a metal spine **2010** in this example to a plastic **2012** used to form a top surface of the connection portion **202**. In this way, the pins in combination with the spine **2010** and plastic **2012** may form a laminate structure that is resistant to bending, e.g., along an axis perpendicular to a surface of the spine **2010** and the heights of the pins. It should be readily apparent that a wide range in the numbers and locations of the pins is contemplated, the previous discussion just one example thereof.

The use of the pins may also support a variety of other functionality. For example, the laminate structure may also be supported through use of an adhesive between the metal spine **2010** and the plastic **2012**. The adhesive, however, may have an amount of time to cure before it is effective. Through use of the pins, however, the adhesive may be applied and then the pins inserted to secure the metal spine **2010** to the plastic **2012** during curing, thereby increasing speed of manufacturing and efficiency. The pins may be configured in a variety of ways, an example of which is described in relation to the following figure.

FIG. **21** depicts an example cross sectional view of the first pin **2002** of FIG. **20** as securing the metal spine **2010** to the plastic of the connection portion **202**. In this example, the first pin **2002** is configured to include self-clinching functionality such that the pin may be secured within a relatively thin material, such as a piece of sheet metal. In this way, the metal spine **2010** may cause a pressure to be applied against a head **2102** of the pin **2102** to secure the first pin **2002** to the metal spine **2010**.

The first pin **2002** may also include a barrel **2104** that is secured within the plastic **2104**. Therefore, the first pin **2002** may be pressed through an appropriate sized hole in the metal spine **2010** to cause the metal spine **2102** to self-clinch as well as the barrel **2104** to be secured within the plastic **2012**. A variety of other types and configurations of pins may be utilized, such as screws, rivets, and so on.

Example System and Device

FIG. **22** illustrates an example system generally at **2200** that includes an example computing device **2202** that is rep-

14

resentative of one or more computing systems and/or devices that may implement the various techniques described herein. The computing device **2202** may be, for example, be configured to assume a mobile configuration through use of a housing formed and size to be grasped and carried by one or more hands of a user, illustrated examples of which include a mobile phone, mobile game and music device, and tablet computer although other examples are also contemplated.

The example computing device **2202** as illustrated includes a processing system **2204**, one or more computer-readable media **2206**, and one or more I/O interface **2208** that are communicatively coupled, one to another. Although not shown, the computing device **2202** may further include a system bus or other data and command transfer system that couples the various components, one to another. A system bus can include any one or combination of different bus structures, such as a memory bus or memory controller, a peripheral bus, a universal serial bus, and/or a processor or local bus that utilizes any of a variety of bus architectures. A variety of other examples are also contemplated, such as control and data lines.

The processing system **2204** is representative of functionality to perform one or more operations using hardware. Accordingly, the processing system **2204** is illustrated as including hardware element **2210** that may be configured as processors, functional blocks, and so forth. This may include implementation in hardware as an application specific integrated circuit or other logic device formed using one or more semiconductors. The hardware elements **2210** are not limited by the materials from which they are formed or the processing mechanisms employed therein. For example, processors may be comprised of semiconductor(s) and/or transistors (e.g., electronic integrated circuits (ICs)). In such a context, processor-executable instructions may be electronically-executable instructions.

The computer-readable storage media **2206** is illustrated as including memory/storage **2212**. The memory/storage **2212** represents memory/storage capacity associated with one or more computer-readable media. The memory/storage component **2212** may include volatile media (such as random access memory (RAM)) and/or nonvolatile media (such as read only memory (ROM), Flash memory, optical disks, magnetic disks, and so forth). The memory/storage component **2212** may include fixed media (e.g., RAM, ROM, a fixed hard drive, and so on) as well as removable media (e.g., Flash memory, a removable hard drive, an optical disc, and so forth). The computer-readable media **2206** may be configured in a variety of other ways as further described below.

Input/output interface(s) **2208** are representative of functionality to allow a user to enter commands and information to computing device **2202**, and also allow information to be presented to the user and/or other components or devices using various input/output devices. Examples of input devices include a keyboard, a cursor control device (e.g., a mouse), a microphone, a scanner, touch functionality (e.g., capacitive or other sensors that are configured to detect physical touch), a camera (e.g., which may employ visible or non-visible wavelengths such as infrared frequencies to recognize movement as gestures that do not involve touch), and so forth. Examples of output devices include a display device (e.g., a monitor or projector), speakers, a printer, a network card, tactile-response device, and so forth. Thus, the computing device **2202** may be configured in a variety of ways to support user interaction.

The computing device **2202** is further illustrated as being communicatively and physically coupled to an input device **2214** that is physically and communicatively removable from

15

the computing device **2202**. In this way, a variety of different input devices may be coupled to the computing device **2202** having a wide variety of configurations to support a wide variety of functionality. In this example, the input device **2214** includes one or more keys **2216**, which may be configured as pressure sensitive keys, mechanically switched keys, and so forth.

The input device **2214** is further illustrated as include one or more modules **2218** that may be configured to support a variety of functionality. The one or more modules **2218**, for instance, may be configured to process analog and/or digital signals received from the keys **2216** to determine whether a keystroke was intended, determine whether an input is indicative of resting pressure, support authentication of the input device **2214** for operation with the computing device **2202**, and so on.

Various techniques may be described herein in the general context of software, hardware elements, or program modules. Generally, such modules include routines, programs, objects, elements, components, data structures, and so forth that perform particular tasks or implement particular abstract data types. The terms “module,” “functionality,” and “component” as used herein generally represent software, firmware, hardware, or a combination thereof. The features of the techniques described herein are platform-independent, meaning that the techniques may be implemented on a variety of commercial computing platforms having a variety of processors.

An implementation of the described modules and techniques may be stored on or transmitted across some form of computer-readable media. The computer-readable media may include a variety of media that may be accessed by the computing device **2202**. By way of example, and not limitation, computer-readable media may include “computer-readable storage media” and “computer-readable signal media.”

“Computer-readable storage media” may refer to media and/or devices that enable persistent and/or non-transitory storage of information in contrast to mere signal transmission, carrier waves, or signals per se. Thus, computer-readable storage media refers to non-signal bearing media. The computer-readable storage media includes hardware such as volatile and non-volatile, removable and non-removable media and/or storage devices implemented in a method or technology suitable for storage of information such as computer readable instructions, data structures, program modules, logic elements/circuits, or other data. Examples of computer-readable storage media may include, but are not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other optical storage, hard disks, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or other storage device, tangible media, or article of manufacture suitable to store the desired information and which may be accessed by a computer.

“Computer-readable signal media” may refer to a signal-bearing medium that is configured to transmit instructions to the hardware of the computing device **2202**, such as via a network. Signal media typically may embody computer readable instructions, data structures, program modules, or other data in a modulated data signal, such as carrier waves, data signals, or other transport mechanism. Signal media also include any information delivery media. The term “modulated data signal” means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media include wired media such as a

16

wired network or direct-wired connection, and wireless media such as acoustic, RF, infrared, and other wireless media.

As previously described, hardware elements **2210** and computer-readable media **2206** are representative of modules, programmable device logic and/or fixed device logic implemented in a hardware form that may be employed in some embodiments to implement at least some aspects of the techniques described herein, such as to perform one or more instructions. Hardware may include components of an integrated circuit or on-chip system, an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), a complex programmable logic device (CPLD), and other implementations in silicon or other hardware. In this context, hardware may operate as a processing device that performs program tasks defined by instructions and/or logic embodied by the hardware as well as a hardware utilized to store instructions for execution, e.g., the computer-readable storage media described previously.

Combinations of the foregoing may also be employed to implement various techniques described herein. Accordingly, software, hardware, or executable modules may be implemented as one or more instructions and/or logic embodied on some form of computer-readable storage media and/or by one or more hardware elements **2210**. The computing device **2202** may be configured to implement particular instructions and/or functions corresponding to the software and/or hardware modules. Accordingly, implementation of a module that is executable by the computing device **2202** as software may be achieved at least partially in hardware, e.g., through use of computer-readable storage media and/or hardware elements **2210** of the processing system **2204**. The instructions and/or functions may be executable/operable by one or more articles of manufacture (for example, one or more computing devices **2202** and/or processing systems **2204**) to implement techniques, modules, and examples described herein.

CONCLUSION

Although the example implementations have been described in language specific to structural features and/or methodological acts, it is to be understood that the implementations defined in the appended claims is not necessarily limited to the specific features or acts described. Rather, the specific features and acts are disclosed as example forms of implementing the claimed features.

What is claimed is:

1. An input device comprising:

an input portion configured to generate signals to be processed by a computing device; and

a connection portion attached to the input portion using a flexible hinge, the connection portion configured to be communicatively coupled to the computing device to communicate the generated signals and physically coupled to the computing device using a projection, formed at least in part from a plastic material, that is configured to be disposed within a channel formed in a housing of the computing device and a spine, formed using metal, that is secured to the projection using a plurality of pins to form a laminate structure with the projection.

2. An input device as described in claim 1, wherein the spine is further secured to the projection using an adhesive.

3. An input device as described in claim 1, wherein at least one of the plurality of pins is configured to be self-clinching to secure the pin as part of the spine.

17

4. An input device as described in claim 3, wherein the at least one of the plurality of pins that is self-clinching is configured such that when secured to the spine, a head of the pin is flush to a surface of the spine.

5. An input device as described in claim 1, wherein the connection portion includes a magnetic coupling device to magnetically couple the input device to the computing device.

6. An input device as described in claim 1, wherein the connection portion includes a plurality of communication contacts to communicate the generated signals to the computing device.

7. An input device as described in claim 1, wherein the connection portion is configured to include one or more protrusions that are configured to be received within respective cavities of the channel of the computing device to resist removal of the connection portion from the computing device along one or more axes.

8. An input device comprising:

an input portion configured to generate signals to be processed by a computing device; and

a connection portion attached to the input portion, the connection portion configured to be communicatively coupled to the computing device to communicate the generated signals, the connection portion comprising:

a projection configured to be disposed within a channel formed in a housing of the computing device to physically couple the connection portion to the computing device;

a plurality of magnets that are configured to form a magnetic attachment with one or more magnets disposed in the channel; and

a spine that is secured to the projection using a plurality of pins along an approximate longitudinal axis defined by a length of the projection.

9. An input device as described in claim 8, wherein the projection, the spine, and the plurality of pins form a laminate structure.

10. An input device as described in claim 8, wherein the securing of the spine to the projection using the plurality of pins causes the projection to have increased mechanical stiffness along the longitudinal axis.

11. An input device as described in claim 8, wherein the spine is further secured to the projection using an adhesive.

18

12. An input device as described in claim 8, wherein the projection is formed at least in part from a plastic material and the spine is formed using metal.

13. An input device as described in claim 8, wherein at least one of the plurality of pins is configured to be self-clinching to secure the pin as part of the spine.

14. An input device as described in claim 13, wherein the at least one of the plurality of pins that is self-clinching is configured such that when secured to the spine, a head of the pin is flush to a surface of the spine.

15. An input device as described in claim 8, wherein the connection portion includes a magnetic coupling device to magnetically couple the input device to the computing device.

16. An input device as described in claim 8, wherein the connection portion includes a plurality of communication contacts to communicate the generated signals to the computing device.

17. An input device comprising:

an input portion configured to generate signals to be processed by a computing device; and

a connection portion attached to the input portion, the connection portion configured to be communicatively coupled to the computing device to communicate the generated signals, the connection portion comprising:

a projection configured to be disposed within a channel formed in a housing of the computing device to physically couple the connection portion to the computing device;

a plurality of magnets that are configured to form a magnetic attachment with one or more magnets disposed in the channel; and

a spine that is secured to the projection using a plurality of pins, the plurality of pins oriented generally perpendicular to a surface of the projection.

18. An input device as described in claim 17, wherein the projection, the spine, and the plurality of pins form a laminate structure.

19. An input device as described in claim 17, wherein the securing of the spine to the projection using the plurality of pins causes the projection to have increased mechanical stiffness along an axis that is defined by the surface of the projection.

* * * * *